

Product Data Sheet

Astro Nu-Guard AG

Revision 4 - 30th September 2021



Astro Nu-Guard AG

Anti-Graffiti Paint.

- Tough resilient finish.
- Available in a clear colour.
- Zero Ghosting - wash graffiti away with water.
- No mixing required.
- In most cases only one coat is required.
- Graffiti can be removed quickly and no-re-application is required.



Product Description

Astro Nu-Guard AG is a anti-graffiti coating that protects all surfaces, including brick, concrete, render, stone, wood and plastic against all types of graffiti and poster glues. Its been completely engineered in the UK to provide the most vandol resistant finish ever achieved anywhere in the world.

Once coated with Astro Nu-Guard AG, nothing can stick to the surface. Astro Nu-Guard AG is completely resistant to ALL paints, permanent markers and the majority of acids. Simple wash with water and graffiti disappears and posters just slide off, providing permanent protection against graffiti attack - without ghosting residue.

Astro Nu-Guard AG is one of the most economical and easy to use anti graffiti products available on the market today

Astro Nu-Guard®AG is ideal for the following applications:

- **Aluminum Siding**
- **Fibreglass**
- **Glass**
- **Masonry (includes brick, marble, stone, tile, granite and concrete)**
- **Metal**
- **Street Signs**
- **Stucco**
- **Utility Boxes**
- **Vinyl Siding**
- **Wood**

Product Availability

Single component product, supplied in 5 litre cans.

Product Code	Product Description	Size
AFAGPNG	Astro Nu-Guard AG	5 LITRE

To Order & Specify

Please contact us and quote the following information - Quantity / Product Code / Product Description / Size
Typical example:- 10 / AFAGPNG / Astro Nu-Guard AG / 5 LITRE

>> Tel: [01329 844 500](tel:01329844500) or >> Email: sales@astroflame.com

Preparation & Application

- **USES:**
Most surfaces can be protected with just one coat of Nu-Guard AG Clear, giving quick application and protection from Graffiti and fly posting.
- **VOLUME SOLIDS:**
70%
- **COVERAGE RATE:**
One thick coat @ 8 m² / Litre
WFT – 125 microns
DFT – 90 microns
- **DRYING TIME:**
Touch Dry :.....1-2 Hours
Full Cure :.....6 Hours
- **PREPARATION:**
Ensure surfaces to be treated are clean, free from contamination and dry.
- **APPLICATION:**
By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.
- **GRAFFITI REMOVAL:**
Graffiti should be removed using warm soapy water. If using a pressure washer, no more than 70bar should be used.

Equipment and Storage

All equipment should be cleaned with white spirit. Store away from direct sunlight and sources of heat. Protect from frost. Do not allow moisture into the tin.

SHELF LIFE: 12 months (in original sealed container).

Health and Safety

Please see (SDS) Safety Data sheet - This can be requested from our sales team T: [01329 844 500](tel:01329844500)
or E: sales@astroflame.com

As part of our policy of ongoing improvements, we reserve the right to modify, alter or change product specifications without giving notice. Product illustrations are representations only. All information contained in this document is provided for guidance only, and as ASTROFLAME (FIRE SEALS) LTD has no control over the specific application or installation methods of the products, or of the prevailing site conditions, no warranties expressed or implied are intended to be given as to the actual performance of the products mentioned or referred to, and no liability whatsoever will be accepted for any loss, damage or injury arising from the use of the information given of products mentioned or referred to herein.

The above information to the best of our knowledge is true and accurate and based upon current test data and is supplied for your guidance only. Customers should satisfy themselves to the suitability of the product based on the products limitation of applications and that the product is fit for purpose for their intended use and no guarantee is given or implied since the conditions of actual use are beyond our control. ASTROFLAME (FIRE SEALS) LTD, disclaim any liability for loss, damage or other expense arising from the use of information, data or products mentioned or referred to and reserve the right to change any details or specifications without notice. If you are in any doubt as to the suitability of this product for your intended application please contact our technical team on 01329 844500 or email sales@astroflame.com and we will contact you.